



# LATICRYL

LATEX ADHESIVE BASED ON ACRYLIC RESINS FOR CEMENTITIOUS MORTAR

## PROBLEM

Often there are problems of adhesion to surfaces when refurbishing with different types of mortar, perhaps because the surface is too smooth, too crumbly or simply old and inconsistent.

## DESCRIPTION

LATICRYL is a resin-based latex dispersed in water and used to make mortar with superior properties of resistance, adhesion and waterproofing to traditional types.

## FIELDS OF USE

LATICRYL is used to:

- improve the characteristics of cementitious mixes for screeds, plaster, smoothing coats or renders;
- improve adhesion and waterproofing of OSMOSEAL osmotic cement;
- improve adhesion of shrink-resistant mortars used for concrete refurbishment.



1. Concrete surface.



2. Old masonry

## PRECAUTIONS

- Use LATICRYL at temperatures between +4°C and +40°C.
- Protect the product from frost.
- Do not use pure LATICRYL as a primer or on top of a primer.
- Wash tools with water after use.

## SAFETY REGULATIONS

- Protect hand and eyes with gloves and goggles.
- Ventilate the workplace adequately.
- In case of contact with eyes, wash immediately and thoroughly with water.
- Keep the product out of reach of children.

## METHOD OF USE

### SUBSTRATE PREPARATION

Clean the surface of dirt, dust, efflorescence, oil and grease.

### MIX PREPARATION

LATICRYL is usually diluted with

water depending on use before being mixed with dry mixtures of cement and inert materials.


LATICRYL is usually mixed with water in a ratio of 1:2 but in some ca-

ses it can be used pure (without any dilution) to give maximum adhesion and waterproofing qualities.

# LATICRYL

## TECHNICAL CHARACTERISTICS

Appearance	milky liquid
Colour	white
Residual solid (DIN 53189)	30%
Viscosity	0.1 Pas
pH	9.5-10
Dispersion density (DIN 51757)	1.04 g/cm <sup>3</sup>
Resistance to ageing	good
Resistance to light	good
Shelf life in original packaging	12 months



WATERPROOF



WATER-BASED



MINIMUM APPLICATION TEMPERATURE



KEEP AWAY FROM FROST

## ADVANTAGES

- Improves adhesion and waterproofing of cementitious mortars.
- Improves mechanical resistance to abrasion.
- Reduces the possibility of cracking.
- Maximum compatibility with cementitious mortars.

## PRODUCT



## PACKAGING


20 kg pails.  
5 kg cans.  
12 bottle boxes × 1 kg each.

**index**  
Construction Systems


Via G. Rossini, 22  
37060 Castel D'Azzano (VR) - Italy  
Tel. 045.8546201 - Fax 045.512444

INTERNET: <http://www.index-spa.com> - E-MAIL: [index.export@index-spa.it](mailto:index.export@index-spa.it)


• FOR ANY FURTHER INFORMATION OR ADVICE ON PARTICULAR APPLICATIONS, CONTACT OUR TECHNICAL OFFICE  
• IN ORDER TO CORRECTLY USE OUR PRODUCTS, REFER TO INDEX TECHNICAL SPECIFICATIONS




Restoration of damp masonry using damp-proofing renders



Waterproofing with vapour permeable cements



Concrete refurbishment



TOTAL QUALITY  
Q.S. ISO 9001

ring the numerous possible uses and the possible interference of conditions or elements beyond our control, we assume no responsibility regarding the results which are obtained. The purchasers, of their own accord and under their own responsibility, must establish the suitability of the product for the envisaged use.

The figures shown are average indicative figures relevant to current production and may be changed or updated by INDEX S.p.A. at any time without previous warning. The advice and technical information provided, is what results from our best knowledge regarding the properties and the use of the product. Consider